## Incandescent Well Lights



#### The CF's superior design and fire-resistant

materials help reduce the risk of fires. The integral honeycomb grate serves to prevent debris build up and provides superior glare protection. Exclusive halogen PAR36 lamps are available in both 20 and 35 Watts. Where the typical PAR36 lamp is rated at 300-3000 hours, the halogen lamp is rated at 4,000 hours. This rail system allows for easy lamp access and fine tuning.


## CF: Well Light



#### The Best House on the Block

Fully encapsulated lamp housing keeps terminals and lamp from being stuck in the mud. This is a very common source of system problems with inferior PAR36 well light products. The CF is versatile – flip the housing and the grate fits both sides.

This lighting fixture is rated for transient landscape moisture-it is not an underwater light.





# CF: Well Light

#### **FACTORY INSTALLED OPTIONS:** Order 1 + 2 + 3

Step	Description	Code
1	FIXTURE	CF
2	LAMP	20 (40° beam), 35 (40° beam) All 4,000 Hr Halogen
3	FINISH	CB, DT

EXAMPLE: CF-20-CB = CF - 20W Halogen Lamp - Camo Bronze Finish

## COMPOSITE



**CB** = Camo Bronze



 $\mathbf{DT} = \mathsf{Desert} \, \mathsf{Tan}$ 

The CF includes choice of halogen PAR36 lamp and choice of finish.

#### **INSTALLATION NOTE:**

### Angled Installation



#### Flat Installation



For application flexibility, the CF can be installed at either end. The grate and lamp will fit both the angled or flat side of the CF body.

Note: Composite finishes cannot be powder coated

