




FACEPLATE



CONSTRUCTION SLEEVE



DETAIL LEGEND:

- ① FX LUMINAIRE "LM" FIXTURE PER PLAN
- ② DIRECT BURY UF/UL, COPPER, LOW VOLTAGE CABLE WITH UL 486D (IEC/EN 60998) RATED WATERPROOF CONNECTION. LEAVE 8" MINIMUM WIRE LOOP COILED IN CONSTRUCTION SLEEVE FOR FUTURE SERVICE.
- ③ ELECTRICAL CONDUIT PER LOCAL CODE
- ④ 12 GA MAIN LINE CABLE

NOTES

- A. FIXTURE REQUIRES 10-15V AC/DC
- B. INSTALL TO A UL 1838 (IEC/EN 61437) LISTED TRANSFORMER
- C. IF WALL IS STUCCOED OR COATED, USE THE "CONSTRUCTION COVER" TO KEEP CAVITY CLEAN AND CLEAR OF DEBRIS.
- D. THIS FIXTURE IS DESIGNED FOR DOWN LIGHTING ONLY. DO NOT USE IN UP LIGHT POSITION.



LED WALL LIGHT (LM) CONCRETE WALL MOUNT

FXLuminaire. W.LM.02

NOT TO SCALE
REV: 2020-07-17